

L4060HST * * EQUIPMENT IN STANDARD MACHINE * *

DIESEL ENGINE

Model # V2403CRE4GL2/GL3
Tier IV Engine
Common Rail Direct Injection
w/ DPF and EGR
4 Cyl., 148.5 cu. in.
^ 40.0 Net Eng. HP
^ 32.5 PTO HP
@ 2600 Eng. rpm
12V 40Amp - 582CCA
Radial Air Flow Cooling
Dual Air Cleaner Element
HYDRAULICS
Open Center
Tandem Pump Gear Type
4.7 gpm Power Steering
9.4 gpm Remote/3 Pt. Hitch
14.1 gpm Total Hyd. Flow
Category I 3-Pt. Hitch
Lift Capacity —
At lift Point 3858 lbs.
24" Behind 2756 lbs.

FRONT AXLE

Hydrostatic Power Steering
Cast iron 4WD front axle
Tread Spacing – Non-adjustable
Bevel Gear drive

DRIVE TRAIN

HST PLUS
3 Forward / 3 Reverse
Hi-Med-Low Range
Mech. Wet Disc Brakes
Clutch - Single Dry Plate
Differential Lock
FLUID CAPACITY
Fuel Tank 13.5 gal.
Cooling System 7.9 qts.
Crankcase 8.7 qts
Transmission and
Hydraulics 11.4 gal.
Front Axle Differential 6.9 qts.
^ Manufacturer Estimate

POWER TAKE OFF

1 Speed Rear Live — HYD.IND.
540 rpm @ 2550 Eng. rpm
SAE 1-3/8 6 Splines
Electric over Hydraulic PTO
Switch
DIMENSIONS
Overall Height w/ROPS 97.6"
Overall Length w/3pt. 129.5"
Wheel Base 74.6"
Crop Clearance 15.9"

IntelliPanel™

Lighted Communications
Symbols
Standard Tachometer
Digital Read for Speed, MPH,
PTO
speeds, diagnostics system
and
DPF system
Warning Symbols

STANDARD EQUIPMENT

ROPS w/Retractable Seat Belt
Highback Adj. Swivel Seat w/Deluxe
Suspension w/Arm Rests
Operator Presence Control System
Parking Brakes
Flat Deck w/ Hanging Pedals
Tilt Steering
Wide Anti-Slip Step
ISO Mounted Platform
Turn Signals / Hazard Flashers
SMV Sign
Telescoping Lower Links
2 Tier Halogen Head Lights
4 Position Loader Valve
One Piece Metal Hood
Cruise Control
Auto Throttle Advance
Hydro Dual Speed (H-DS)
HST Response control
Throttle-Up Switch

**Call For Current Rebates
& Finance Specials**

Suggested List Price w/ Options:

\$34,166



FREE
6-YEAR
POWERTRAIN
WARRANTY
ON ALL COMPACT UTILITY TRACTORS

OUR PRICE

\$29,999

**Farm Depot 275 Columbia
Caro, MI 989-673-6172**