

MX5200HST * * * EQUIPMENT IN STANDARD MACHINE

* * *

D
Turbo charged with Wastegate Valve and DPF system 4 Cyl. 148.6 cu. in. + 52.1 Net Eng. HP +44.2 PTO HP HST @ 2700 Eng. rpm EPA Tier 4 Final Emission Cert. Direct Injection (CRS) 12V – 582 CCA Battery Charging Output 40 Amps
HYDRAULICS Open Center — Gear Type Dual Pumps 4.8 gpm Power Steering 9.2 gpm Remote/3 Pt. Hitch 14.0 gpm Total Hyd. Flow Cat II/I 3-point Hitch with cushion relief valve At lift Point 2866 lbs. 24" Behind 2310 lbs. Telescoping Lower Links Stabilizers + Manufacturer Estimate

Transmission Low/Medium/High Cruise Control Std. Mech. Wet Disc Brakes Left Side Brake Pedals (HST) Differential Lock Std.
FLUID CAPACITY Fuel Tank 14.3 gal Cooling System 7.9 qts Crankcase 8.0 qts Transmission and Hydraulics 11.6 gal Front Axle (DT/HST) 7.9 qts
POWER TAKE OFF Live-Independent ElectroHydraulic Engagement 540 rpm Rear PTO@ 2700 Eng. rpm SAE Std 1 3/8" Six Spline
SAFETY EQUIPMENT 2-Post Foldable ROPS w/ Retractable Seat Belt Flip-Up PTO Shield Safety Start Switches PTO – OPC Operator Presence Control Alarm Parking Brakes Electric Key Shut Off Turn Signals SMV Sign

w/Hanging Pedals High Back Seat with Adjustable Suspension Color Coded Controls
INSTRUMENTS Tachometer/Hour Meter LCD Display Fuel Gauge Charge/Oil Pressure Parking Brakes Indicator Light

SELECTED TIRES AMXR8828 & AMXR8862 INDUSTRIAL TIRES
FRONT - 12-16.5 R4 Titan HD-2000
REAR - 17.5L-24 R4 Titan Industrial Contractor TL

FRONT AXLE Hydrostatic Power Steering 2WD: Tubular Steel Beam Adj. (Telescoping) Tread Spacing 4WD: Bevel Gear Cast Iron Non-Adjustable Tread Spacing

MX5200HST Base Price: \$28,659.00

LA1065-FRONT LOADER \$4,739.00

L2236-72" QUICK ATTACH LIGHT MATERIAL BUCKET \$649.00 FACTORY ASSEMBLY \$250.00

Suggested List Price w/ Options: \$34,297.00

Call For Current Rebates & Finance Specials



6-YEAR ^{FREE}
POWERTRAIN
WARRANTY
ON ALL COMPACT UTILITY TRACTORS

OUR PRICE

\$30,499

Farm Depot 275 Columbia
Caro, MI 989-673-6172